

Übersicht SGM-Park

	Schließkraft	Spritzvolumen	Holmabstand	max. Abstand Aufspannplatten	Abmessungen Aufspannplatten	Spritzdruck	Min. Einbauhöhe	Schneckendurchmesser	Auswerferhub
	[kN]	[cm³]	[mm]	[mm]	H x B [mm]	[spez. bar]	[mm]	[mm]	[mm]
2	250	25	holmlos	480	380 x 360	2.220	150	18	70
		67	270	475	498 x 498	2.210	200	30	95
1	300	49	HL	500	550 x 400	1.600	150	25	100
1	450	99	HL	500	450 x 350	2.200	150	30	100
4	500	59	320	650	450 x 450	2.500	200	30	100
		85	320	550	450 x 450	2.000	200	30	125
		49	270	550	450 x 450	2.240	200	25	125
		69	HL	500	500 x 450	2.090	200	25	100
1	800	139	420	700	560 x 560	2.500	250	35	150
1	900	154	HL	750	420 x 550	2.200	250	35	130
4	1.000	132	420	750	430 x 420	1.820	250	35	175
		101	420	700	430 x 420	2.500	250	30	150
		144	420	750	430 x 420	2.500	250	30	175
		102	420	750	430 x 420	2.500	250	30	175
1	1.200	154	HL	800	470 x 550	1.600/2.175	300	35	130
1	1.250	510	HL	850	700 x 530	2.051	250	55	130
1	1.300	251	470	900	600 x 480	2.500	300	40	150
1	1.500	254	470	750	700 x 700	1.580	250	45	175
1	1.600	318	565	950	700 x 550	2.336	300	45	150
2	2.000	510	HL	1150	760 x 720	2.051	450	55	150
		392	570	950	650 570	2.000	350	50	175
1	2.200	618	HL (600)	1050	830 x 610	1.763	300	55	180
1	2.500	392	630	900	900 x 900	2.000	550	50	225
2	3.500	664	720	800	1.040 x 1.040	2.000	300	60	250
1	4.200	792	800	1400	800 x 800	2.420	380	60	250
1	6.500	1.239	1.040 x 910	1.350 / 800	1.400 x 1.350	2.420	400	70	250